


Concord

ASCENT 100 II DECO 900 4K STD EMG 120
2060616



Features

- The ASCENT 100 II DECO 900 4K STD EMG 120 is a high efficient non dimmable downlight luminaire with 3 hour emergency, Colour rendering index Ra >80, Colour temperature: 4000K Neutral White, Class II, Protection rating IP40/IP20, Cut out dimensions: 137mm

Product Overview

Product name	ASCENT 100 II DECO 900 4K STD EMG 120
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Fixture luminous flux (lm)	931
Luminaire efficacy (lm/W)	93
LOR (%)	100
Colour temperature (K)	4000
CRI (Ra)	80
Colour Consistency (SDCM)	3
Glare control	< 22
Photobiological Risk Group	RG0
Total power consumption (W)	10
Electrical protection	Class II
Control gear type	Electronic ballast
Control gear mounting	Remote
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP40/20

Concord

ASCENT 100 II DECO 900 4K STD EMG 120
2060616

IK rating

IK02


Product EAN number

5025768606160


Warranty

5 years

Photometry



Technical drawings



Data table

Concord

ASCENT 100 II DECO 900 4K STD EMG 120 2060616

GENERAL DATA

Product name	ASCENT 100 II DECO 900 4K STD EMG 120
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Operating temperature range (°C)	0°C...+25°C
Performance ambient temperature Tq (°C)	25
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	931
Luminaire efficacy (lm/W)	93
LOR (%)	100
Colour temperature (K)	4000
CRI (Ra)	80
Colour Consistency (SDCM)	3
Glare control	< 22
Photobiological Risk Group	RG0

ELECTRICAL DATA

Total power consumption (W)	10
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.90
Electrical protection	Class II
Control gear required	No
Control gear type	Electronic ballast
Control gear mounting	Remote
Drive current (mA)	150
Inrush Current (A)	8
Glow Wire Test (°C)	650

Concord

ASCENT 100 II DECO 900 4K STD EMG 120 2060616

Energy Efficiency Class (A->G) of contained light source	C
--	---

Nominal Frequency (Hz)	50/60Hz
------------------------	---------

LIFETIME DATA

Lifespan L70 B50	100000
------------------	--------

Lifespan L80 B20	87500
------------------	-------

Lifespan L90 B10	39000
------------------	-------

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
----------------	----------------------------------

IP rating	IP40/20
-----------	---------

IK rating	IK02
-----------	------

Diffuser finish	Opal
-----------------	------

Diffuser material	PMMA Acrylic
-------------------	--------------

Nominal Product Width (mm)	150
----------------------------	-----

Nominal Product Diameter (mm)	150
-------------------------------	-----

Weight (kg)	1.43
-------------	------

PACKAGING

Single packaging type	Carton
-----------------------	--------

Product EAN number	5025768606160
--------------------	---------------

Packaging single width (cm)	30.0
-----------------------------	------

Packaging single depth (cm)	12.5
-----------------------------	------

DUN14 (outer)	05025768606160
---------------	----------------

Packaging outer length / height (cm)	30.0
--------------------------------------	------

SAFETY DATA

Special purpose lamp	No
----------------------	----

Dry applications use only	No
---------------------------	----

Suitable for household illumination	No
-------------------------------------	----