

2C-0404: Wall plate horizontal 1/2"X1/2"



Commercial information

Wallplate horizontal 1/2"x1/2"

Basic unit dimensions

Height	49 mm
Length	32 mm
Width	49 mm
Net weight	0.093 kg

Certificates

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Length	32 Millimetre
Surface protection connection 1	Untreated	Wrench width	0 Millimetre
Surface treatment connection 1	Untreated	Wrench width union nut	0 Millimetre
Material connection 2	Brass	Tightening torque	0 0 Newtonmetre
Material quality connection 2	CuZn40Pb2 (CW617N)	Medium temperature (continuous)	-10 60 Degrees celsius
Surface protection connection 2	Untreated	Max. operating pressure at 20 °C	10 Bar
Surface treatment connection 2	Untreated	Standard Dimension Ratio (SDR)	0
Reducing	✘		
Eccentric	✘		
System specific	✔		
Nominal diameter connection 1	1/2 inch (15)		
Connection 1	Internal thread cylindrical BSPP-G (ISO 228-1)		
Nominal diameter connection 2	1/2 inch (15)		
Connection 2	Internal thread cylindrical BSPP-G (ISO 228-1)		
Main colour fitting	Brass		
With buffer stud	✔		
High tensile strength	✘		
With thermal insulation	✘		
With sealing rings/gaskets	✔		
Capped	✘		
With connection indicator	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✘		
KIWA certified	✘		
Gastec QA mark	✘		
KOMO certified	✘		
Type approval according to BBR/EKS	✘		