



### Features

- Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps
- Omnidirectional 320° uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubes
- High lumen package - 2000lm
- High lumen efficacy - 100 lm/W
- Energy rating - A+
- Switching cycles - 200,000X
- Average life 40,000 hours lifespan (L70 F50)
- Wide beam angle - 220°
- High power factor - 0.90
- Suitable for general illumination in offices, supermarkets, department stores, train stations, petrol stations, parking lots and maintenance free applications
- Suitable for operation with electromagnetic gears and direct mains operation (220-240V)
- 3-Year warranty.

### Product Overview

Product name	TOLEDO T8 V6 4FT 20W 2000LM 865 RL
Technology	LED
Watt (Rated) (W)	20
Cap/Base	G13
E-number FI	4940743
Colour temperature (K)	6500
CRI (Ra)	80
Wattage (W)	20
Product EAN number	5410288282886
Warranty	3 years

### Data table

#### GENERAL DATA

Product name	TOLEDO T8 V6 4FT 20W 2000LM 865 RL
Technology	LED
Watt (Rated) (W)	20

## TOLEDO T8 V6 4FT 20W 2000LM 865 RL 0028288

Cap/Base	G13
E-number FI	4940743
Warranty	3 years

### OPTICAL DATA

Luminous flux (Rated) (lm)	2000
Colour temperature (K)	6500
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70

### ELECTRICAL DATA

Wattage (W)	20
Starting time (max) (s)	0.5
Lamp power factor	0.9
Control gear required	No

### LIFETIME DATA

Average life (Rated) (h)	40000
--------------------------	-------

### PHYSICAL DATA

Weight (kg)	0.208
-------------	-------

### PACKAGING

Single packaging type	Carton
Product EAN number	5410288282886
Packaging single width (cm)	2.9
Packaging single depth (cm)	2.9
DUN14 (outer)	15410288282883
Packaging outer length / height (cm)	129.7

### SAFETY DATA

TOLEDO T8 V6 4FT 20W 2000LM 865 RL  
**0028288**

---

<b>Breakage cleaning instructions</b>	Not applicable
<b>Special purpose lamp</b>	No
<b>Dry applications use only</b>	No
<b>Suitable for household illumination</b>	No
<b>Safety message</b>	Suitable for totally enclosed fixture