

# Product data sheet Spirotech

## Product name

**EVSG Expansion vessel 250L**

## Product properties

Pressure expansion vessels with replaceable membrane, P max. 3 bar / T max. 70°C

## Article number

**EVSG250**

## Product image



## Product dimensions

# Product data sheet Spirotech

## ETIM product data

|                                       |                                                |
|---------------------------------------|------------------------------------------------|
| Height                                | 1090 mm                                        |
| Volume                                | 250 l                                          |
| Colour                                | Other                                          |
| Diameter                              | 600 mm                                         |
| Max. operating pressure               | 3 bar                                          |
| Connection                            | Internal thread cylindrical BSPP-G (ISO 228-1) |
| With pressure gauge                   | No                                             |
| With exchangeable membrane            | Yes                                            |
| Nominal diameter expansion connection | 3/4 inch (20)                                  |
| Horizontal positioning                | No                                             |
| Suitable for central heating          | Yes                                            |
| Vertical positioning                  | Yes                                            |

|                                      |                                                |
|--------------------------------------|------------------------------------------------|
| With legs                            | Yes                                            |
| Material membrane/bladder            | Ethylene-propylene diene monomer rubber (EPDM) |
| With drain                           | No                                             |
| With safety valve                    | No                                             |
| With mounting material               | No                                             |
| Max. glycol mixture                  | 60 %                                           |
| Suitable for tap water               | No                                             |
| Max. ethanol mixture                 | 60 %                                           |
| Suitable for solar collector circuit | No                                             |
| Pre-pressure                         | 1.3 bar                                        |
| With fixed wall support              | No                                             |
| Suitable for cooling                 | No                                             |

### Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website.

