

ToLEDo Performer T-Series

ToLEDo Performer T60 2300LM 840 E27 SL

0028369



Product features



- Direct retrofit replacement for high-pressure mercury vapor lamps (HPMV) 50,000 hours average rated lifetime Up to 78% energy saving compared to the standard high-pressure mercury vapor lamps Mercury-free solution Lower maintenance cost High lumen efficacy Dual operating mode - compatible with HPMV magnetic ballast and also, suitable for AC direct mains 120-240V operation High surge voltage protection: 4kV Suitable for both open and enclosed luminaires Wide light distribution High switching cycles - 200,000X High colour rendering - CRI 80 Minimum and maximum operating temperature: -30°C to 50°C



PRODUCT OVERVIEW

Product name	ToLEDo Performer T60 2300LM 840 E27 SL
Technology	LED
Watt (Rated) (W)	18
Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Logistics & Industry
ETIM Class	EC001959
E-number FI	4844489
Warranty	5 years
Luminous flux (lm)	2300
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Wattage (W)	18
Dimmable	No
Average life (Nominal) (h)	50000
Product EAN number	5410288283692

PHOTOMETRY



ToLEDo Performer T-Series

ToLEDo Performer T60 2300LM 840 E27 SL

0028369

TECHNICAL DRAWINGS

