



Color: ■ gray

Electrical data

Ratings per IEC/EN

Nominal voltage (III/3)	400 V
Rated impulse voltage (III/3)	6 kV
Rated current	24 A

Physical data

Width	14.5 mm / 0.571 inches
Height	6 mm / 0.236 inches
Jumper assignment	1-4

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.011 MJ
Weight	1.8 g

Commercial data

Product Group	17 (TOP JOB Installation Terminal Blocks)
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-14-11-40
ETIM 8.0	EC000489
ETIM 7.0	EC000489
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918270922
Customs tariff number	85366990990



Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 780-454	↓

Documentation

Additional Information		
Technical Section	pdf 2240.62 KB	↓


Bid Text			
780-454	19.02.2019	xml 2.91 KB	↓
780-454	28.04.2017	doc 24.00 KB	↓

CAD/CAE-Data

CAD data		CAE data	
2D/3D Models 780-454	↓	EPLAN Data Portal 780-454	↓
		WSCAD Universe 780-454	↓
		ZUKEN Portal 780-454	↓

Installation Notes

Commoning



Staggered jumpers are suitable for sophisticated circuit requirements. Push jumpers down until fully inserted!

Staggered jumpers are suitable for sophisticated circuit requirements. Push jumpers down until fully inserted!