

Giotto LED 335
GIOTTO 335 4000K SURFACE 1-10V
3034800



Product features

- Ambient and decorative round, surface mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 2350lm, 20.3W, 116lm/W, 4000K, CRI 80, 1-10V dimmable, 120,000 hours lumen maintenance (L70:B50). Drive current: 600mA, IP44, IK10, Class I, 220-240V.




PRODUCT OVERVIEW

| | |
|-----------------------------------|--|
| Product name | GIOTTO 335 4000K SURFACE 1-10V |
| Technology | LED |
| Cap/Base | N/A |
| Housing | PC Polycarbonate |
| Mount | Ceiling surface mounting, Wall surface mounted |
| Environment | Indoor |
| General application | Hospitality, Logistics & Industry |
| ETIM Class | EC002892 |
| E-number FI | 4270258 |
| Warranty | 5 years |
| Useful luminous flux (Fuse) | 2350 |
| Fixture luminous flux (lm) | 2350 |
| Luminous flux (lm) | 2350 |
| Luminaire efficacy (lm/W) | 116 |
| Correlated colour temperature (k) | 4000 |
| Colour Code | 840 |
| Light colour | Neutral White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Beam Angle (°) | 120 |
| Glare control | < 26 |
| Photobiological Risk Group | RG0 |
| Total power consumption (W) | 20.3 |
| Electrical protection | Class I |
| Control gear type | LED driver constant current |
| Control gear mounting | Integrated |
| Dimmable | Yes |
| Dimming method | 1-10V (Analogue) |
| LED Flickering Rate | Ultra low (5% or less) |
| Housing colour | White |
| IP rating | IP44 |
| IK rating | IK10 |
| Product EAN number | 8711971348009 |

Giotto LED 335
GIOTTO 335 4000K SURFACE 1-10V
3034800

PHOTOMETRY



TECHNICAL DRAWINGS

