

Rana Helios 600

RANA HELIOS R 600 2L LOUV+PRI
0044994



Product features

- Ceiling recessed luminaire, dimensions: 595 x 595 x 52mm, white (RAL9016) coated body, satin aluminium reflector (double symmetrical light distribution), for 2 x Helios LED T5 lamps (lamps not included), constant current LED driver, low LED flicker (+/-5%), 150mA drive current, push-in connector, IP20, IK07




PRODUCT OVERVIEW

Product name	RANA HELIOS R 600 2L LOUV+PRI
Technology	LED
Cap/Base	G5
Housing	Steel
Mount	Ceiling recessed mounting
General application	Education, Office
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	3100
Luminaire efficacy (lm/W)	141
Correlated colour temperature (k)	4000
Light colour	N/A
CRI (Ra)	85
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	46
Glare control	< 19
Photobiological Risk Group	RG1
Light source included	Fixture without Lightsource
Total power consumption (W)	22
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288449944

Rana Helios 600

RANA HELIOS R 600 2L LOUV+PRI
0044994

PHOTOMETRY



TECHNICAL DRAWINGS

