

Twofold faceplate, horizontal 71 mm centre distance, for one 45x45 function and a double switch function, Niko Rocker and Niko Toggle steel white coated

155-57808



The Niko Rocker and Niko Toggle twofold horizontally oriented faceplate clicks onto one 45 x 45 mm function and a double switch function that have been horizontally installed next to each other with a centre distance of 71 mm. The faceplate combines with any available Niko 45 x 45 mm function and a Niko Rocker and Niko Toggle double switch function. It consists of an upper frame and lower frame that are mechanically interconnected. The upper frame is made of steel. The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated. The upper frame is 2 mm thick and the lower frame 6 mm.



Niko recommends a design combination with a finishing set in the following colour: white coated.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)
- Designed to fit any available 45 x 45 mm function

Technical data

Twofold faceplate, horizontal 71 mm centre distance, for one 45x45 function and a double switch function, Niko Rocker and Niko Toggle steel white coated.

- Double faceplate for two switches.
- Colour faceplate: steel white coated
- Colour RAL (approximately): 000 90 00
- Colour NCS (approximately): NCS S 1002-B50G
- Recommended colour central plate: white coated
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material finishing: The upper frame is made of steel. The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated.

- Surface treatment: coated
- Surface finishing: matt
- Coating upper frame: the upper frame is enamelled white
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Surface-mounting height: max. 8.5 mm
- Halogen-free: yes
- Fire safety:
 - self-extinguishing: complies with a filament test of 650°C
- Centre-to-centre distance: 60 mm
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP21D
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Minimum ambient temperature: 5 °C
- Maximum ambient temperature: 40 °C
- Dimensions (HxWxD): 143 mm x 83 mm x 8.9 mm
- Dimensions visible (HxWxD): 143 mm x 83 mm
- Marking: EU