


29022902	DATA SHEET
Valid from: 23.07.2026	GOF DUPLEX Patchcord ST/ST E9 OS2, 2m

Description

- GOF Optical fiber Patchcord
- Straight ST-Duplex-plug on straight ST-Duplex-plug



General characteristics

Connection method, connector	ST-Duplex (ST-D), metal
Polishing	ST-Duplex (ST-D), metal
Fiber type	UPC (Ultra Physical Contact)
Number of conductors	Singlemode E9 OS2
Temperature range	2
	-25°C to +70°C (-13°F to 158°F) (Operation)
	-25°C to +70°C (-13°F to 158°F) (Storage)
	-10°C to +60°C (14°F to 140°F) (Installation)

Additional note

Standard length 2m. Data sheet also valid for variant lengths.

Optical properties

Insertion loss (max.)	0.25 dB / 0.5 dB (mean/ 97%)
Return loss (min.)	55 dB

Mechanical properties


ST-D-Plug

Housing, material	Hpb59-1
Ferrule, material	Zirconia
Boot, material	TPE, black and blue
Tensile strength	100 N
Mating cycles (min.)	1000

Line

Outer coating, material	LSOH, yellow
Cable outer diameter	2 mm
Min bending radius	50 mm (Installation)
	25 mm (Operation)

Technical drawing



29022902	DATA SHEET
Valid from: 23.07.2026	GOF DUPLEX Patchcord ST/ST E9 OS2, 2m

Standards / Approvals

Fibre optic connector interfaces – Type BFOC/2,5
Optical fibres – part 2-50: class B single-mode fibres

IEC 61754-2
IEC 60793-2-50

Application range

Office, Data centers, Industry

Note

Photographs are not true to scale and do not represent detailed images of the respective products.