



START Surface Wall Cube IP54 2x140lm 2CCT White

Item No: 0047137


SYLVANIA

START




Technical Assets

Dimensions (mm)



Photometrics



START Surface Wall Cube IP54 2x140lm
2CCT White

Item No: 0047137

SYLVANIA

General data

Product name	START Surface Wall Cube IP54 2x140lm 2CCT White
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Wall surface mounted
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+45°C
ETIM Class	EC002892
E-number FI	4579606
Warranty	5 years

Optical data

Fixture luminous flux (lm)	280
Luminaire efficacy (lm/W)	48
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Adjustable
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	5.8
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.66
Electrical protection	Class I
Control gear type	LED driver constant current
Dimming method	N/A
Inrush Current (A)	10
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	70
Max. products per 13A C Breaker	86
Max. products per 16A C Breaker	100
Max. products per 20A C Breaker	100
Max. products per 20A B Breaker	96
Connectable conductor cross section - Max (mm²)	1.5

Lifetime data

Lifespan L70 B50	104000
Lifespan L70 B20	101000
Lifespan L70 B10	98700
Lifespan L80 B50	68000
Lifespan L80 B20	67000
Lifespan L80 B10	67000
Lifespan L90 B50	36000
Lifespan L90 B20	35000
Lifespan L90 B10	35000

START Surface Wall Cube IP54 2x140lm
2CCT White

Item No: 0047137

SYLVANIA

Physical data

Housing colour	White
IP rating	IP54
IK rating	IK05
Diffuser finish	Transparent
Diffuser material	Glass
Nominal Product Length (mm)	108
Nominal Product Width (mm)	108
Nominal Product Height (mm)	109
Weight (kg)	0.785

Packaging

Product EAN number	5410288471372
Packaging single width (cm)	14.5
Packaging single depth (cm)	14.5
DUN14 (inner)	15410288471379
Packaging outer length / height (cm)	60.0

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-45