


Data Sheet | Item Number: 260-405

Test plug module; with locking latches; modular; for 4-conductor terminal blocks;
for 260 Series; gray

<https://www.wago.com/260-405>



Color: ■ gray

Electrical data

Ratings per IEC/EN

Nominal voltage (III/3) 500 V

Ratings per IEC/EN – Notes

Ratings (note) Maximum test voltage (touch contact): 48 V (test pins are not touch-proof)

Ratings per IEC/EN 2

Ratings (note) Maximum test current (touch contact): 0.5 A
Maximum test current: 6 A (if the test pins are securely connected in the clamping units)

General information

Test voltage 48 V
Test current 0.5 A

Physical data

Width 8 mm / 0.315 inches
Module width 8 mm / 0.315 inches

Material data

Note (material data) [Information on material specifications can be found here](#)
Color gray
Material group I
Insulation material (main housing) Polyamide (PA66)
Flammability class per UL94 V0
Fire load 0.05 MJ
Weight 2.2 g

Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data

Product Group	9 (Std Chassis Mt Blocks)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4050821868941
Customs tariff number	85366990990

Product Classification

UNSPSC	39121409
eCl@ss 10.0	27-14-11-48
eCl@ss 9.0	27-14-11-48
ETIM 9.0	EC002555
ETIM 10.0	EC002555
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	e07b893f-be2f-4454-8072-4b10b0fa609e
SCIP notification number (Belgium)	e1d61b71-7865-4db9-9cec-c528084fa2b6
SCIP notification number (Bulgaria)	0149ed8b-8344-400f-9c67-64e741b5e615
SCIP notification number (Czech Republic)	a6c88aa7-21a5-47fa-a2ed-41c4be095ad0
SCIP notification number (Denmark)	a5d5f2da-0b25-4781-b194-056cd57c7180
SCIP notification number (Finland)	3b8d99ca-c3db-431c-96f8-5c97af64c379
SCIP notification number (France)	7da2dbe5-d58b-4024-b275-465a6983e0ec
SCIP notification number (Germany)	c6ec24e1-4823-43cd-91e8-489e983a621e
SCIP notification number (Hungary)	e1f86406-e382-4f38-a758-5b6cc465be31
SCIP notification number (Italy)	cf30e572-c93a-4ce8-a89d-7ad0c2a595b5
SCIP notification number (Netherlands)	4178d072-e438-4587-99a4-e09362a22392
SCIP notification number (Poland)	10355f43-60e4-4085-a4e3-9e9f1c08f554
SCIP notification number (Romania)	609718c7-fee8-461d-93b2-925c2da4dad1
SCIP notification number (Sweden)	8ffaa56f-9fc8-4af5-b210-9735018269fa

Downloads

Environmental Product Compliance



Compliance Search

Environmental Product
Compliance 260-405



Documentation

Bid Text

260-405	19.02.2019	xml 3.17 KB	
260-405	18.08.2017	doc 24.00 KB	

CAD/CAE-Data

CAE data

WSCAD Universe
260-405



1 Compatible Products

1.1 Optional Accessories

1.1.1 Test and measurement


1.1.1.1 Testing accessories



Item No.: 210-136

Test plug; 2 mm Ø; with 500 mm cable; red

Installation Notes



Testing via test plug modules snapped onto a terminal strip – wired or unwired. As touch contact is made with the CAGE CLAMP® (spring steel) unit, this testing type is limited to maximum 0.5 A.

Distance between locking devices must be approximately 35 ... 40 mm!



Testing after the conductors have been terminated.