

ZODIAC MEDIUM G2 13KLM 4000K CLI GREY
0049978



Features

• The Zodiac family is dedicated for road/area lighting applications. Light distribution: Asymmetric Medium for roads, color temperature: 4000K , total system power: 93W, total fixture lumen output: 13200lm, luminaire efficacy: 142lm/W, colour rendering index: 70, LED Chromaticity: 5 step MacAdam ellipse tolerance, lumen maintenance: 50000 hours at L70:B50 @ 25°C, operating voltage: 220-240V / 50-60Hz, operating temperature range: -35 - +50°C, non-dimmable, power factor: min. 0.9, electrical protection: Class I, Ingress protection rating: IP66, Impact resistance: IK08, dimensions (LxWxH): 675x292x101mm, net weight: 6.2kg, for 42-60mm side entry or post top installation with +/-15° adjustability, the housing is made of Die Cast Aluminium in RAL9022 color combined with tempered flat glass cover.


Product Overview

Product name	ZODIAC MEDIUM G2 13KLM 4000K CLI GREY
Technology	LED
Cap/Base	N/A
Housing	Aluminium
E-number FI	4579577
Fixture luminous flux (lm)	13200
Luminaire efficacy (lm/W)	142
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	70
Colour Variation Initial (SDCM)	5
Photobiological Risk Group	RG1
Total power consumption (W)	93
Electrical protection	Class I
LED Flickering Rate	Ultra low (5% or less)

ZODIAC MEDIUM G2 13KLM 4000K CLI GREY
0049978

Housing colour	Grey
IP rating	IP66
IK rating	IK08
Product EAN number	5410288499789
Warranty	5 years

Photometry



Technical drawings

