

47P-25H26: Transition Coupling U-TH-H 25x2,5mm to Henco 26x3,0



Commercial information

Basic unit dimensions

Height	33 mm
Length	72 mm
Width	33 mm
Net weight	0.116 kg

Certificates

KIWA

Applications

Potable water, Heating, Compressed air, Cooling, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Bend angle	0 Degrees
Surface protection connection 1	Untreated	Bend radius	0 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 1	25 Millimetre
Material connection 2	Brass	Outer pipe diameter connection 2	26 Millimetre
Surface protection connection 2	Untreated	Wall thickness connecting pipe, connection 2	3 Millimetre
Surface treatment connection 2	Untreated	Length	72 Millimetre
Shape	Straight	Medium temperature (continuous)	-10 70 Degrees celsius
Model	1-part	Max. operating pressure at 20 °C	16 Bar
Reducing	✓	Max. operating pressure at max. medium temperature	16 Bar
Eccentric	✗		
System specific	✗		
Connection 1	Press sleeve		
Connection 2	Press sleeve		
Contour code connection 2	TH		
Main colour fitting	Brass		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With thermal insulation	✗		
With sealing rings/gaskets	✓		
Capped	✗		
With connection indicator	✓		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
Certified according to NF 545	✗		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Gastec QA - AR 214 (H2)	✗		
Type approval according to BBR/EKS	✗		