



Color: ■ gray

Similar to illustration

### Electrical data

Operating voltage	250 VAC
Power (max.)	0.6 W
Thermal resistance	140 K/W
Tolerance	±1%
Resistor type/design	DIN 0207

### Safety and protection

Rated surge voltage	4 kV
Pollution degree	3
Protection type	IP20

### Connection data

Actuation type	Operating tool
----------------	----------------

### Physical data

Width	10 mm / 0.394 inches
-------	----------------------

### Material data

Color	gray
Insulation material	Polyamide (PA66)
Material group	I
Flammability class per UL94	V0
Fire load	0.141 MJ
Weight	4.2 g

**Environmental requirements**

Ambient temperature (operation)	-25 ... +70 °C
Processing temperature	-35 ... +85 °C

**Standards and specifications**

Standards/specifications	EN 60947-7-1 EN 60664-1 EN 60558
--------------------------	--

**Commercial data**

Product Group	1 (Rail Mounted Terminal Blocks)
PU (SPU)	50 pcs
Country of origin	DE
GTIN	4045454196127
Customs tariff number	85369010000

**Environmental Product Compliance**

RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	7(c)-I

**Downloads****Environmental Product Compliance****Compliance Search**

Environmental Product  
Compliance  
280-803/281-707

