Product data sheet Spirotech

Product name

EMCC Maxi-1 max 5,6bar

Product properties

The MultiControl COOL MAXI is an automatic expansion and pressure-maintaining device, with 2 pumps (2x 100%) and 1 overflow valve, designed for cooling systems. A separate storage tank is required.

- 2 pumps (2x 100%)
- 1 overflow valve (1x 100%)
- Operational pressure range up to 4,0 or 5,6 bar
- An unpressurized expansion vessel is required
- Maximum expansion volume: 125 500 liters
- The minimum temperature at the point of connection: -10°C
- The maximum temperature at the point of connection: 70°C (over 70°C possible with auxiliary tank)
- Maximum operating pressure (PN): 10 bar


Article number

EMCC-M1-5.6

Product image



Product dimensions





Product data sheet Spirotech

ETIM product data

Height	1244 mm
Max. operating pressure	5.6 bar
Connection	Other
Power consumption	1.5 kW
Couplable	Yes
Electrical connection	Terminals
Function master/slave	No
With pressure expansion vessel	No
Digital control unit	Yes
Double pump/compressor unit	Yes

With exchangeable membrane	No
Compressor in base	No
Nominal diameter expansion connection	1 inch (25)
Max. medium temperature (continuous)	70 °C
For heating systems up to	1 MW
Horizontal positioning	No
Connection voltage	230 V
Article compression class	PN 10
Operating principle	Pump

Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website.



