

ToLEDo Performer T-Series
ToLEDo Performer T85 4500LM 840 E27 SL
0028371



Product features


- Direct retrofit replacement for high-pressure mercury vapor lamps (HPMV)50,000 hours average rated lifetimeUp to 78% energy saving compared to the standard high-pressure mercury vapor lampsMercury-free solutionLower maintenance costHigh lumen efficacyDual operating mode - compatible with HPMV magnetic ballast and also, suitable for AC direct mains 120-240V operationHigh surge voltage protection: 4kVSuitable for both open and enclosed luminairesWide light distributionHigh switching cycles - 200,000XHigh colour rendering - CRI80Minimum and maximum operating temperature: -30°C to 50°C



PRODUCT OVERVIEW

Product name	ToLEDo Performer T85 4500LM 840 E27 SL
Technology	LED
Watt (Rated) (W)	36
Cap/Base	E27
Fixture rating	Open
General application	Logistics & Industry
ETIM Class	EC001959
E-number FI	4740740
Warranty	5 years
Useful luminous flux (Fuse)	4500
Luminous flux (lm)	4500
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Power consumption (W)	36
Wattage (W)	36
Dimmable	No
Average life (Nominal) (h)	50000
Product EAN number	5410288283715

PHOTOMETRY



ToLEDo Performer T-Series

ToLEDo Performer T85 4500LM 840 E27 SL
0028371

TECHNICAL DRAWINGS

