



Color: ■ silver-colored

Similar to illustration

### Electrical data

#### Ratings per IEC/EN

|               |      |
|---------------|------|
| Rated current | 32 A |
|---------------|------|

### Physical data

|                   |                     |
|-------------------|---------------------|
| Pin spacing       | 5 mm / 0.197 inches |
| Jumper assignment | 1-2                 |

### Mechanical data

|          |                                     |
|----------|-------------------------------------|
| Suitable | for 745 Series (4 mm <sup>2</sup> ) |
|----------|-------------------------------------|

### Material data

|                      |                                                                                                                        |
|----------------------|------------------------------------------------------------------------------------------------------------------------|
| Note (material data) | <a href="https://www.wago.com/us/material-specifications">Information on material specifications can be found here</a> |
| Color                | silver-colored                                                                                                         |
| Contact material     | Copper alloy                                                                                                           |
| Contact plating      | Tin                                                                                                                    |
| Fire load            | 0 MJ                                                                                                                   |
| Weight               | 0.8 g                                                                                                                  |

### Commercial data

|                       |                                |
|-----------------------|--------------------------------|
| Product Group         | 4 (Printed Circuit Connectors) |
| eCl@ss 10.0           | 27-14-11-40                    |
| eCl@ss 9.0            | 27-44-04-92                    |
| ETIM 8.0              | EC000489                       |
| ETIM 7.0              | EC000489                       |
| PU (SPU)              | 250 (50) pcs                   |
| Packaging type        | Box                            |
| Country of origin     | CH                             |
| GTIN                  | 4044918303279                  |
| Customs tariff number | 85366990990                    |

| Environmental Product Compliance |                         |
|----------------------------------|-------------------------|
| RoHS Compliance Status           | Compliant, No Exemption |

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 745-182

↓

Documentation

Additional Information

|                   |            |                   |   |
|-------------------|------------|-------------------|---|
| Technical Section | 03.04.2019 | pdf<br>2010.85 KB | ↓ |
|-------------------|------------|-------------------|---|

CAD/CAE-Data

CAD data

2D/3D Models 745-182


↓

CAE data


ZUKEN Portal 745-182

↓


Installation Notes



Inserting a comb-style jumper bar.



To insert a comb-style jumper bar, push it down using a screwdriver until it hits the backstop – 745 Series.



To remove the jumper bar, lift it up using a screwdriver – 745 Series.