

Product data sheet

Item No. 92.238.4014.3

Cable assembly GST18I3K1-S 25W 40GR01

geis® Connection cable male - free end; length: 4m; type GST18I3; 3-pole; 250 V / 20 A; colour of coding: grey with grey strain-relief; cable:H05V2V2-F 3G2,5, colour: black



| | |
|------------|---------------|
| Item No. | 92.238.4014.3 |
| EAN | 4015573856509 |
| Order Unit | 15 Piece(s) |

Certificates / Approvals

Technical data

General

| | |
|--|-------------|
| Rated current | 20 A |
| Rated voltage | 250 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 2 |
| Mechanical coding | Code 2 |
| Interlockable | Yes |
| Color of coding/ contact carrier | Pebble gray |
| Marking of poles | |
| Color of housing inclusive strain relief | Pebble gray |

Model

| | |
|---------------------------------|-------------------------------------|
| Number of poles | 3 |
| Nominal cross section conductor | 2.5 mm ² |
| Degree of protection (IP) | IP40 |
| Wire strip length | 9 mm |
| sheath strip length | 35 mm |
| Preparation of conductor ends | Ultrasonically compressed wire ends |
| Cable type | H05V2V2-F |
| Cable colour | Black |
| Cable diameter | 10.2 mm |

| | |
|---------------------|------------------|
| Version of cable | Male - free end |
| Type of cord set | Connection cable |
| Version cable end 2 | Free end |

Material

| | |
|--|------------|
| Surface finish | Tin-plated |
| Halogen free | No |
| Continuous temperature of cable | 90 °C |
| Insulation components continuous temperature | 100 °C |

Dimensions

| | |
|--------------|-----|
| Total length | 4 m |
|--------------|-----|