

## Start Flood Flat without PIR


Start Flood Flat IP65 4650LM 830 White  
0050119



### PRODUCT OVERVIEW

Product name	Start Flood Flat IP65 4650LM 830 White
Technology	LED
E-number FI	4579549
Warranty	3 years
Fixture luminous flux (lm)	4650
Luminaire efficacy (lm/W)	103
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Photobiological Risk Group	RG1
Total power consumption (W)	45
Electrical protection	Class I
LED Flickering Rate	Low (6% - 20%)
Housing colour	White
IP rating	IP65
IK rating	IK06
Product EAN number	5410288501192

### PHOTOMETRY



Distance [m]	Cone diameter [m]	E101 E100	E100 E100	E100 E100
0.5	1.54 1.51	676	642	671
1.0	3.08 3.01	169	155	162
1.5	4.62 4.52	76	69	73
2.0	6.16 6.02	42	38	40
2.5	7.70 7.53	26	23	24
3.0	9.24 9.03	17	15	16

Distance [m] Cone diameter [m] Illuminance [lx]  
 — C0 - C180 (Half beam angle: 112.0°)  
 — C90 - C270 (Half beam angle: 114.0°)

## Start Flood Flat without PIR

*Start Flood Flat IP65 4650LM 830 White*

0050119

### TECHNICAL DRAWINGS

---

