

START DOWNLIGHT IP44 225

START Downlight 225 IP44 2325lm 840
0030331



Product features

- Ceiling recessed LED downlight IP44 (from the front), perfect where limited ceiling void is available with only 65mm product depth and 225mm cutout. Ideal replacement for 2x26W CFL downlights. The polycarbonate diffuser allows for a wider light distribution and increased spacings between luminaires. Loop in loop out connector allows for quick installation. Die-cast aluminium body, 2325LM, 23W, 101lm/W, 4000K, Driver Current: 630mA, CRI80, 74° beam angle, Non-dimmable LED driver, IP44 from the front, IK07, (HxW) 65x225mm, Class 2, 220-240V. Meets TP(a) requirements.



PRODUCT OVERVIEW

Product name	START Downlight 225 IP44 2325lm 840
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Logistics & Industry, Office
ETIM Class	EC001744
E-number FI	4278156
Warranty	5 years
Fixture luminous flux (lm)	2325
Luminous flux (lm)	2325
Luminaire efficacy (lm/W)	101
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	74
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	23
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9010 - Pure white
IP rating	IP44/20
IK rating	IK07
Product EAN number	5410288303314

START DOWNLIGHT IP44 225


START Downlight 225 IP44 2325lm 840
0030331

PHOTOMETRY

0.5	0.83	E:0° E:C0°	39.7°	536	1564
1.0	1.66	E:0° E:C0°	39.7°	1214	391
1.5	2.49	E:0° E:C0°	39.7°	661	228
2.0	3.32	E:0° E:C0°	39.7°	319	73
2.5	4.15	E:0° E:C0°	39.7°	204	47
3.0	4.98	E:0° E:C0°	39.7°	142	31

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 79.4°)



TECHNICAL DRAWINGS

