

## CU-REGC-RF: Thermostat Lcd, Optional Ext. Sensor, Incl. 2x AAA batt



### Commercial information

Thermostat LCD, optional ext. sensor

#### Basic unit dimensions

Height	27 mm
Length	85 mm
Width	85 mm
Net weight	0.130 kg

#### Certificates

#### Applications

Heating, Cooling, Underfloor Heating

#### Solutions

Underfloor heating, Building installations, Industry, Utility

## Technical characteristics

Regulation type on/off	✗	Measuring range	0 40 Degrees celsius
Regulation type modulating	✓	Number of heater outputs	1
Communications protocol	Brand-dependent	Number of cooler outputs	1
Type of power supply	Battery	Differential value	2 2 Kelvin
Connection	Wireless	Number of switching programmes	4
With receiver	✓	Max. contact voltage	0 Volt
External sensor	✗	Max. contact load	0 Ampere
With thermal feedback	✗	Width	85 Millimetre
Control characteristic	Other	Depth	85 Millimetre
Suitable for heating	✓	Height	27 Millimetre
Suitable for heating	✓	Standby power consumption (solstandby)	0 Watt
Suitable for cooling	✓		
Adjustable differential	✓		
Selector switch for heating and heating with hot water	✗		
Sensor/feeler type	Resistance sensor		
Temperature readable	✓		
Relative humidity (RH) readable	✗		
With display	✓		
Type of clock	Week clock		
Clock model	Digital		
Overtime switch	✗		
Optimisation	✗		
With tap water circuit	✗		
Operation	Button		
Weather-dependent control system	✗		
Contact type	Normally open contact (NO)		
Degree of protection (IP)	IP20		
Degree of protection (NEMA)	3		
Explosion-proof	✓		
Colour	White		
Compatible with Apple HomeKit	✗		
Compatible with Google Assistant	✗		
Compatible with Amazon Alexa	✗		
IFTTT support available	✗		