


1PK-1414: Elbow 90° 14x14



Commercial information

PVDF press fittings in combination with multilayer pipe, a completely corrosion-free system. The synthetic press fittings are made from injection moulded PVDF (Polyvinylidene fluoride)*. PVDF offers the user a unique combination of properties:

- Highly resistant to pressure and temperature
- Excellent mechanical strength
- Extreme flexibility: bending up to 10° is possible
- Perfectly suited for drinking water and food
- Highly resistant to chemicals and corrosion
- Embedding is possible without extra protection

Certificates

ATG, QB (CSTBat), DVGW Wasser, ETA, KIWA, ÖVGW Wasser, SINTEF, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, AFNOR, PZH, ACS, DNV-GL, Aenor, Sans 21003, Kontrol Biro, EMI

Applications

Potable water, Heating, Compressed air, Cooling, Demi Water, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Polyvinylidene fluoride (PVDF)	Bend radius	7 Millimetre
Material quality connection 1	Polyvinylidene fluoride (PVDF) (expired)	Outer pipe diameter connection 1	14 Millimetre
Surface protection connection 1	Untreated	Wall thickness, connection 1	0.75 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 2	14 Millimetre
Material connection 2	Polyvinylidene fluoride (PVDF)	Wall thickness, connection 2	0.75 Millimetre
Material quality connection 2	Polyvinylidene fluoride (PVDF) (expired)	Zeta value	3.071
Surface protection connection 2	Untreated	Length	56 Millimetre
Surface treatment connection 2	Untreated	Length of connection 1	46.5 Millimetre
Shape	Bend	Working length connection 1	25 Millimetre
Reducing	✗	Length of connection 2	46.5 Millimetre
Eccentric	✗	Working length connection 2	25 Millimetre
System specific	✓	Wrench width	0 Millimetre
Nominal diameter connection 1	DN 10	Wrench width union nut	0 Millimetre
Connection 1	Press sleeve	Tightening moment	0 0 Newtonmetre
Contour code connection 1	TH/BE	Medium temperature (continuous)	-10 70 Degrees celsius
Nominal diameter connection 2	DN 10	Max. operating pressure at 20 °C	16 Bar
Connection 2	Press sleeve	Max. operating pressure at max. medium temperature	10 Bar
Contour code connection 2	TH/BE	Standard Dimension Ratio (SDR)	0
Main colour fitting	Black		
Flange compression class	Other		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
High tensile strength	✗		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With connection indicator	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		

Related products

Product code	GTIN	Description
BE14	05414764022560	Henco Jaws (universal) BE/TH-Profile 14x2

Image



PRESSCHECK1432	05414764022560	Henco Tool to control the accuracy of a pressing Ø14-32
----------------	----------------	---



