


Walraven Maxx Bolt Set (ZFC)

(H20528)

for fixing to Maxx Heavy Rail Profiles



Features & benefits

- for fixing in profile perforation
- when tightening directly onto Maxx profiles, it is strongly advised to use Maxx U-shape brackets
- hexagon head bolt set with 2 washers and hexagon nut for Maxx profile connections
- the bolt size is ideally suited to fit the perforation of Maxx Heavy Rail Profile
- max. torque is 80Nm
- material: steel, strength class 8.8
- surface treatment: zinc flake coated
- consists of: 1 Bolt DIN931, 1 hexagon nut DIN934, 2 washers 37x3mm (M12) or 50x3mm (M16)

Product Number	For Rail Type	Model	Total Width x Total Height x Total Length	Thread Length	Thread Size	Length	Width Across Flats
Reference letter			W x H x L	TL	TS	L	WAF
Unit description			mm x mm x mm	mm		mm	mm
614581212	80x80	Maxx 80 Bolt Set	20 x 20 x 120	30	M12	120	19
614581213	100x100	Maxx 100 Bolt Set	20 x 20 x 147.5	36	M12	140	19
614581216	100x120	Maxx 120 Bolt Set	20 x 20 x 167.5	36	M12	160	19
614581612	80x80	Maxx 80 Bolt Set	35 x 35 x 130	38	M16	120	24
614581614	100x100	Maxx 100 Bolt Set	25 x 25 x 150	44	M16	140	24
614581616	100x120, 100x150	Maxx 120 Bolt Set	25 x 25 x 170	44	M16	160	24