

Features

- The streamlined, durable, lightweight die-cast aluminium body makes Start Flood Flat a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black (RAL9017) housing, white reflector, 5000 lm, 42 W, 119 lm/W, 4000K, non dimmable, CRI>80, IP65, IK06, Class I, lifespan L70:B50: 120000 hrs, 122 x 156 x 28 mm (L x W x H). Weight: 0.445 kg.

Product Overview

Product name	Start Flood IP65 5000LM 840 Black
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling surface mounting, Wall surface mounted
Fixture luminous flux (lm)	5000
Luminaire efficacy (lm/W)	119
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Photobiological Risk Group	RG1
Total power consumption (W)	42
Electrical protection	Class I
Control gear type	Not required
Housing colour	Black
IP rating	IP65
IK rating	IK06

Start Flood IP65 5000LM 840 Black 0050165


Product EAN number

5410288501659

Warranty

3 years

Photometry



Technical drawings

