


Threefold faceplate, horizontal 71 mm centre distance, for a single and a double switch function and a socket outlet function, Niko Toggle steel white coated

154-57718



The Niko Toggle threefold horizontally oriented faceplate clicks onto a single and a double switch function and a socket outlet function that have been horizontally installed next to each other with a centre distance of 71 mm. The faceplate combines with any available Niko Toggle for single and double switch functions and and Niko Rocker and Niko Toggle socket outlet finishing set. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upperframe is made of steel. The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated. The upper frame is 2 mm thick and the lower frame 6 mm.



Niko recommends a design combination with a finishing set in the following colour: steel white coated for Niko Rocker and Niko Toggle finishing sets and white coated for other finishing sets.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)
- Designed to fit the standard socket outlet base

Technical data

Threefold faceplate, horizontal 71 mm centre distance, for a single and a double switch function and a socket outlet function, Niko Toggle steel white coated.

- Threefold faceplate for three switches.
- Colour faceplate: steel white coated
- Colour RAL (approximately): 000 90 00
- Colour NCS (approximately): NCS S 1002-B50G
- Recommended colour central plate: steel white coated for Niko Rocker and Niko Toggle finishing sets and white coated for other finishing sets
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.

- Material finishing: The upperframe is made of steel. The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated.
- Surface treatment: coated
- Surface finishing: matt
- Coating upper frame: the upper frame is enamelled white
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Centre-to-centre distance: 71 mm
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP21D
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 mm x 225 mm x 13 mm
- Dimensions visible (HxWxD): 83 mm x 225 mm
- Certification marks: CEBEC, NF
- Marking: EU