



46P-3228P: Bend compression x copper press (M,V,SA) 32x28 cusi



Commercial information

Henco brass press fittings - the best solution for every situation.

46P Brass (CW724) transition pieces bend 90° Henco compression to copper press (V-, M- and SA-profile):

- Suitable for Henco multilayer pipes diameter 26 and 32 mm
- Body material: brass CW724
- Material press sleeves: stainless steel
- Material O-rings: EPDM
- Connection 1: Henco compression 26 or 32 mm
- Connection 2: copper press 22 or 28 mm
- Permitted press profiles: V, M or SA for copper pipe diameter 22 and 28 mm
- Suitable for drinking water and heating
- Press connection equipped with leak detection (Leak Before Press functionality)
- Extremely pressure and temperature resistant
- Equipped with shock ring to prevent electrolysis

Basic unit dimensions

Height	68 mm
Length	21 mm
Width	49 mm
Net weight	0.443 kg

Certificates

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Utility, Shipbuilding, Industry

Technical characteristics

Material connection 1	Brass	Bend radius	90 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 1	32 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 2	28 Millimetre
Material connection 2	Brass	Wall thickness, connection 2	1.4 Millimetre
Surface protection connection 2	Untreated	Length	20.7 Millimetre
Surface treatment connection 2	Untreated	Medium temperature (continuous)	-10 70 Degrees celsius
Shape	Bend	Max. operating pressure at 20 °C	10 Bar
Reducing	✗	Standard Dimension Ratio (SDR)	0
Eccentric	✗		
System specific	✓		
Connection 1	Compression ring		
Connection 2	Press sleeve		
Main colour fitting	Brass		
Material sealing	Brass		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✗		
Gastec QA mark	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		