


RANA Linear Surface&Suspended - MicroPrismatic Optic
RANA LINEAR S 3KLM NW MPO
0051250



PRODUCT OVERVIEW

Product name	RANA LINEAR S 3KLM NW MPO
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Fixture rating	Enclosed
Environment	Internal
E-number SE	7502669
Warranty	5 years
Fixture luminous flux (lm)	3100
Luminaire efficacy (lm/W)	100
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Glare control	< 21
Photobiological Risk Group	RG0
Total power consumption (W)	31
Electrical protection	Class I
Control gear type	Electronic ballast
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288512501

DATA TABLE

General data	
Product name	RANA LINEAR S 3KLM NW MPO

RANA Linear Surface&Suspended - MicroPrismatic Optic

RANA LINEAR S 3KLM NW MPO

0051250

Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Fixture rating	Enclosed
Environment	Internal
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
E-number SE	7502669
Warranty	5 years

Optical data

Fixture luminous flux (lm)	3100
Luminaire efficacy (lm/W)	100
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Glare control	< 21
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	31
Primary Supply/Product voltage - min (V)	198
Lamp power factor	0.95
Electrical protection	Class I
Control gear type	Electronic ballast
Drive current (mA)	300
Inrush Current (A)	22
Inrush Duration (µs)	250
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	40
Max. products per 20A B Breaker	48
Connectable conductor cross section - Min (mm²)	2.5
Connectable conductor cross section - Max (mm²)	2.5

Lifetime data

Lifespan L70 B50	60000
Lifespan L70 B20	60000
Lifespan L70 B10	60000



RANA Linear Surface&Suspended - MicroPrismatic Optic
RANA LINEAR S 3KLM NW MPO
0051250

