



## 46P-2622P: Bend compression x copper press (M,V,SA) 26X22 cusi



### Commercial information

Henco brass press fittings - the best solution for every situation.

46P Brass (CW724) transition pieces bend 90° Henco compression to copper press (V-, M- and SA-profile):

- Suitable for Henco multilayer pipes diameter 26 and 32 mm
- Body material: brass CW724
- Material press sleeves: stainless steel
- Material O-rings: EPDM
- Connection 1: Henco compression 26 or 32 mm
- Connection 2: copper press 22 or 28 mm
- Permitted press profiles: V, M or SA for copper pipe diameter 22 and 28 mm
- Suitable for drinking water and heating
- Press connection equipped with leak detection (Leak Before Press functionality)
- Extremely pressure and temperature resistant
- Equipped with shock ring to prevent electrolysis

#### Basic unit dimensions

Height	61 mm
Length	62 mm
Width	41 mm
Net weight	0.290 kg

#### Certificates

#### Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

#### Solutions

Building installations, Utility, Shipbuilding, Industry

## Technical characteristics

Material connection 1	Brass	Bend radius	90 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 1	26 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 2	22 Millimetre
Material connection 2	Brass	Wall thickness, connection 2	1.4 Millimetre
Surface protection connection 2	Untreated	Length	62.2 Millimetre
Surface treatment connection 2	Untreated	Medium temperature (continuous)	-10 70 Degrees celsius
Shape	Bend	Max. operating pressure at 20 °C	16 Bar
Reducing	✗	Standard Dimension Ratio (SDR)	0
Eccentric	✗		
System specific	✓		
Nominal diameter connection 1	DN 25		
Connection 1	Compression ring		
Nominal diameter connection 2	DN 20		
Connection 2	Press sleeve		
Main colour fitting	Brass		
Flange compression class (PN)	PN 10		
Material sealing	Brass		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✗		
Gastec QA mark	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		