

# Productinformatieblad

Specificaties



## TeSys GV2ME - Vermogensschakelaar - Thermisch/ Magnetisch - 0,1-0,16A

GV2P01

EAN Code: 3389110213409

**Prijs: 103,00 EUR**

### Hoofd

range	Tesys deca
product name	TeSys GV2
product or component type	Motor vermogensschakelaar
device short name	GV2P
device application	Motorbeveiliging
trip unit technology	Thermisch-magnetisch

### Complementair

poles description	3P
network type	AC
utilisation category	A conform aan IEC 60947-2 AC-3 conform aan IEC 60947-4-1 AC-3e conform aan IEC 60947-4-1
netfrequentie	50/60 Hz conform aan IEC 60947-2
breaking capacity	100 kA Icu bij 230/240 V AC 50/60 Hz conform aan IEC 60947-2 100 kA Icu bij 400/415 V AC 50/60 Hz conform aan IEC 60947-2 100 kA Icu bij 440 V AC 50/60 Hz conform aan IEC 60947-2 100 kA Icu bij 500 V AC 50/60 Hz conform aan IEC 60947-2 100 kA Icu bij 690 V AC 50/60 Hz conform aan IEC 60947-2
ics dienst kortsluitonderbrekingsvermogen	100 % bij 230/240 V AC 50/60 Hz conform aan IEC 60947-2 100 % bij 400/415 V AC 50/60 Hz conform aan IEC 60947-2 100 % bij 440 V AC 50/60 Hz conform aan IEC 60947-2 100 % bij 500 V AC 50/60 Hz conform aan IEC 60947-2 100 % bij 690 V AC 50/60 Hz conform aan IEC 60947-2
control type	Rotatiehendel
In toegekende stroomsterkte	0,16 A
instelbereik thermische bescherming	0,1...0,16 A conform aan IEC 60947-2
magnetische uitschakelstroom	1,93 A
Ith conventionele thermische stroom in vrije lucht	0,16 A conform aan IEC 60947-2
Ue toegekende bedrijfspanning	690 V AC 50/60 Hz conform aan IEC 60947-2
Ui toegekende isolatiespanning	690 V AC 50/60 Hz conform aan IEC 60947-2
Uimp nom. schokgolfsparing	6 kV conform aan IEC 60947-2
gevoeligheid voor afwezigheid fase	Ja conform aan IEC 60947-4-1
suitability for isolation	Ja conform aan IEC 60947-1
vermogensdissipatie per pool	2,5 W

De weergegeven prijs is de adviesprijs in euro excl. BTW. Deze kan onderhevig zijn aan korting. Neem contact op met uw lokale distributeur of detailhandel voor de daadwerkelijke prijs

mechanical durability	100000 cycles
elektrische duurzaamheid	100000 cycles voor AC-3 bij 415 V In 100000 cycles voor AC-3e bij 415 V In
nominale werking	Ononderbroken conform aan IEC 60947-4-1
aansluitingen - aansluitklemmen	Vermogenskring: schroefklemmaansluitklem 2 kabel(s) 1...6 mm <sup>2</sup> vast Vermogenskring: schroefklemmaansluitklem 2 kabel(s) 1,5...6 mm <sup>2</sup> flexibel zonder kabeluiteinde Vermogenskring: schroefklemmaansluitklem 2 kabel(s) 1...4 mm <sup>2</sup> flexibel met
aanspanmoment	1,7 N.m - op schroefklemmaansluitklem
bevestigingsmethode	35 mm symmetrische DIN-rail: afgesneden Paneel: geschroefd (met 2 schroeven M4)
montagepositie	Horizontaal Verticaal
width	45 mm
height	89 mm
depth	97 mm
colour	Donkergrijs

## Omgeving

normen	EN/IEC 60947-2 EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 Nr 60947-4-1 IEC/EN 60335-2-40:Annex JJ IEC/EN 60335-1:Clause 30.2
product certifications	CCC UL CSA EAC ATEX LROS (Lloyds register of shipping) BV RINA DNV-GL UKCA
IK beschermingsgraad	IK04
IP beschermingsgraad	IP20 conform aan IEC 60529
weerbestedigheid	conform aan IACS E10
ambient air temperature for storage	-40...80 °C
vuurbestedigheid	960 °C conform aan IEC 60695-2-11
ambient air temperature for operation	-20...60 °C
mechanische stevigheid	Schokken: 30 Gn gedurende 11 ms Trillingen: 5 Gn, 5...150 Hz
bedrijfshoogte	<= 2000 m

## Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4,500 cm
Package 1 Width	9,400 cm
Package 1 Length	10,000 cm

Package 1 Weight	264,000 g
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	15,000 cm
Package 2 Width	30,000 cm
Package 2 Length	40,000 cm
Package 2 Weight	5,550 kg
Unit Type of Package 3	P06
Number of Units in Package 3	320
Package 3 Height	75,000 cm
Package 3 Width	60,000 cm
Package 3 Length	80,000 cm
Package 3 Weight	98,500 kg

## contractuele waarborg

Garantie	18 months
----------	-----------

## Environmental Data

Schneider Electric wil tegen 2050 de Net Zero-status hebben bereikt via partnerschappen in de toeleveringsketen, materialen met een lagere impact en circulariteit via onze doorlopende campagne "Use Better, Use Longer, Use Again" om de levensduur van producten en de recycleerbaarheid te verlengen.

[Uitleg van Environmental Data](#) >

[Hoe evalueren we de duurzaamheid van producten?](#) >

### Milieuoetafdruk

Totale levenscyclus ecologische voetafdruk 9

Milieuprofiel van product (PEP) [Milieuprofiel van het product](#)

### Use Better

#### Materialen en verpakking

Pakket met gerecycleerd karton Ja

Verpakkingen zonder kunststof Nee

[EU-richtlijn RoHS](#) Voldoet aan vrijstellingen

REACH-regelgeving [REACH-verklaring](#)

### Use Again

#### Herverpakken en herfabriceren

Circulair Profiel [Informatie over einde levensduur](#)

Terugname No

WEEE Label  Het product moet op markten van de Europese Unie worden afgevoerd volgens specifieke afvalinzamelingsregels en mag nooit in een gewone vuilnisbak terechtkomen.

Offer Marketing Illustration

Product benefits / Features

---

## TeSys Deca Motor Circuit Breakers



### Universal Integration

Can be used for all type of applications across industry, infrastructure and buildings.



### Complete protection

Provide short circuit protection, overload protection, motor (ON/OFF) control, all in a single product.



### Standard Sync

Compliant to motor control and protection, in accordance with standards.



Offer Marketing Illustration

Product benefits / Features

---



**TeSys Deca Motor Circuit Breakers**  
Range Accessories

Auxiliary contact blocks

Energy Sensor

Terminal block

Combination block

Current limiter

Comb busbar

Extended rotary handle

The image displays a collection of accessories for TeSys Deca Motor Circuit Breakers. At the top left, a large circuit breaker is shown with a green arrow pointing to its handle. Below it, seven different accessories are arranged in two rows. Each accessory is accompanied by a small image and a text label. The accessories include auxiliary contact blocks, an energy sensor, terminal blocks, combination blocks, current limiters, a comb busbar, and extended rotary handles.

Offer Marketing Illustration

Product benefits / Features

---



The image shows a TeSys Deca Motor Circuit Breaker, a black industrial device with a green handle. It has three main terminals at the top labeled 1L1, 3L2, and 5L3, and three main terminals at the bottom labeled 2T1, 4T2, and 6T3. A green handle is positioned in the center, with 'ON' and 'OFF' markings. A QR code and the Schneider logo are visible on the front panel.

### TeSys Deca Motor Circuit Breakers

#### Technical Benefits

- High breaking capacity up to 100 kA.
- Screw clamp for the connection, with lug and spring terminals.
- Easily identify the tripped breaker.
- Padlockable in all versions.
- Sealable thermal overload settings without additional accessories.
- Short circuit indication for better diagnostics when a trip occurs.
- Maximum 15 current ratings to cover from 0.1 A to 32 A motor current with a IP20 level for finger safety.

Image of product / Alternate images

Alternative

---





Technical Illustration

Assembly's dimensions

---

