

Threefold faceplate, vertical 71 mm centre distance, for a single and two double switch functions, Niko Rocker steel white coated

154-56953



The Niko Rocker threefold vertically oriented faceplate clicks onto a single and two double switch functions that have been vertically installed on top of each other with a centre distance of 71 mm. The faceplate combines with any available Niko Rocker for single and double switch functions. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upperframe is made of steel. The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated. The upper frame is 2 mm thick and the lower frame 6 mm.

Niko recommends a design combination with a finishing set in the following colour: steel white coated.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)



Technical data

Threefold faceplate, vertical 71 mm centre distance, for a single and two double switch functions, Niko Rocker steel white coated.

- Threefold faceplate for three switches.
- Colour faceplate: steel white coated
- Colour RAL (approximately): 000 90 00
- Colour NCS (approximately): NCS S 1002-B50G
- Recommended colour central plate: steel white coated
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material finishing: The upperframe is made of steel. The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated.
- Surface treatment: coated
- Surface finishing: matt
- Coating upper frame: the upper frame is enamelled white

- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Recess for indication led:
 - the faceplate is fitted with a light guide
 - the light guide is made of a translucent plastic
 - the light guide transports the light from the optional LED to the lever
 - please note that the faceplate should not be mounted upside down to ensure that the optional LED fits nicely with the light guide
- Centre-to-centre distance: 71 mm
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP20D
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 225 mm x 83 mm x 13 mm
- Dimensions visible (HxWxD): 225 mm x 83 mm
- Marking: EU