


Twofold faceplate, horizontal 71 mm centre distance, for one 45x45 function and a double switch function, Niko Rocker steel white coated

154-56808



The Niko Rocker twofold horizontally oriented faceplate clicks onto one 45 x 45 mm function and a double switch function that have been horizontally installed next to each other with a centre distance of 71 mm. The faceplate combines with any available Niko 45 x 45 mm function and a Niko Rocker double switch function. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upperframe is made of steel. The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated. The upper frame is 2 mm thick and the lower frame 6 mm.



Niko recommends a design combination with a finishing set in the following colour: steel white coated for Niko Rocker and Niko Toggle finishing sets and white coated for other finishing sets.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)
- Designed to fit any available 45 x 45 mm function

Technical data

Twofold faceplate, horizontal 71 mm centre distance, for one 45x45 function and a double switch function, Niko Rocker steel white coated.

- Double faceplate for two switches.
- Colour faceplate: steel white coated
- Colour RAL (approximately): 000 90 00
- Colour NCS (approximately): NCS S 1002-B50G
- Recommended colour central plate: steel white coated for Niko Rocker and Niko Toggle finishing sets and white coated for other finishing sets
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material finishing: The upperframe is made of steel. The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated.

- Surface treatment: coated
- Surface finishing: matt
- Coating upper frame: the upper frame is enamelled white
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Recess for indication led:
 - the faceplate is fitted with a light guide
 - the light guide is made of a translucent plastic
 - the light guide transports the light from the optional LED to the lever
 - please note that the faceplate should not be mounted upside down to ensure that the optional LED fits nicely with the light guide
- Centre-to-centre distance: 71 mm
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP20D
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 mm x 154 mm x 13 mm
- Dimensions visible (HxWxD): 83 mm x 154 mm
- Marking: EU