

Product data sheet

Item No. 92.258.1004.1

Cable assembly GST1815KS-S 25 10SW

geis® Connection cable male - free end; length: 1m; type GST1815; 5-pole; 250/400 V / 20 A; colour of coding: black with black strain-relief; cable: H05VV-F 5G2,5, colour: black



Item No.	92.258.1004.1
EAN	4015573351035
Order Unit	30 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	5
Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP40
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F



Cable colour	Black
Cable diameter	12.1 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	GST1815 plug
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	1 m
--------------	-----

Technical drawing

.F	Farbe colour	Codierung	Kabelfarbe cable colour
.1	schwarz black	Stecker male	schwarz black
.2	weiß white	1 2 PE N 3	weiß white

Pol/pole	Aderfarben/color of core
1	braun/brown
2	schwarz/black
3	grau/grey
N	blau/blue
⊕	grün-gelb/green-yellow

Kabel/cable H05VV-F 5G 2,5
Farbe/color: siehe Tabelle/see table

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.258.XX04.F	XX in dm-Schritten	92.258.1004.1 = 10dm/L= 1000mm	GST1815KS-S 25 10SW
U2.258.XX04.F	XX in m-Schritten	U2.258.1204.1 = 12 m/L=12000mm	GST1815KS-S 25 X12SW

Weitere Daten siehe Katalog
further data see catalog

wieland

GST1815

INSTALL. COUPLER
KONFEKTLEITUNG
ST/male-1r./Endy/free end, Schraubanschl./screw connection
KS-S 25 ... 250V AC, 20A, 2,5sqmm