

Features

- Surface or Suspended LED Linear luminaire with Louvre + Micro Prismatic Optic, Dimensions: 1150mm x 87mm x 87mm, Direct, White Body, DALI Dimmable (Switch-Dim), Emergency 3 hours maintained, Neutral White LED (4000K), 3160lm, 31W, 102lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse), Low LED Flicker (+/-5%), UGR<19, L90B10 at 50,000 hours, Electric Class1, Glow Wire Test 850°C


Product Overview

Product name	RANA LINEAR S 3KLM NW LOUV+PRI D EMPRO
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Fixture rating	Enclosed
Environment	Internal
Fixture luminous flux (lm)	3160
Luminaire efficacy (lm/W)	101.93
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	31
Electrical protection	Class I
Control gear type	Electronic ballast

RANA LINEAR S 3KLM NW LOUV+PRI D EMPRO
0051271

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288512716
Warranty	5 years

Photometry



Technical drawings

