

38P-2622P: Adapter henco compression x copper press (M,V,SA) 26x22 cusì



Commercial information

Henco brass press fittings - the best solution for every situation.

38P Brass (CW724) transition pieces straight Henco compression to copper press (V, M and SA profile):

- Suitable for Henco multilayer pipes diameter 26 and 32 mm
- Body material: brass CW724
- Material press sleeves: stainless steel
- Material O-rings: EPDM
- Connection 1: Henco compression 26 or 32 mm
- Connection 2: copper press 22 or 28 mm
- Permitted press profiles: V, M or SA for copper pipe diameter 22 and 28 mm
- Suitable for drinking water and heating
- Press connection equipped with leak detection (Leak Before Press functionality)
- Extremely pressure and temperature resistant
- Equipped with shock ring to prevent electrolysis

Basic unit dimensions

Height	56 mm
Length	39 mm
Width	39 mm
Net weight	0.211 kg

Certificates

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Utility, Shipbuilding, Industry

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material connection 2	Brass	Outer pipe diameter connection 1	26 Millimetre
Shape	Straight	Wall thickness connecting pipe, connection 1	3 Millimetre
Reducing	✓	Outer pipe diameter connection 2	22 Millimetre
Eccentric	✗	Wall thickness, connection 2	1.4 Millimetre
System specific	✓	Length	39.4 Millimetre
Nominal diameter connection 1	DN 25	Medium temperature (continuous)	-10 70 Degrees celsius
Connection 1	Compression ring	Max. operating pressure at 20 °C	16 Bar
Nominal diameter connection 2	DN 20	Standard Dimension Ratio (SDR)	0
Connection 2	Press sleeve		
Main colour fitting	Brass		
Flange compression class (PN)	PN 10		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✗		
Gastec QA mark	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		