

## EzLogger3000C

GoodWe's EzLogger3000C is designed for data acquisition, transmission, and protocol conversion in commercial and industrial (C&I) PV projects. It enables seamless communication with utility cloud servers, allowing real-time monitoring, remote control, and efficient power dispatching.



Connecting up to 100 devices



Support of multiple protocols



Data breakpoint resume



USB and embedded web for data reading and software upgrade

Model	EzLogger3000C
<b>Device Management</b>	
Max. Number of Connected Devices	100
<b>Electrical</b>	
Power Adapter	AC Input: 100 ~ 240V, 50 / 60Hz DC Output: 24V
DC Power Supply (V)	24
Power Consumption (W)	<15
<b>Communication Interface</b>	
LAN	2
RS485	COM x 4
WIFI (local maintenance)	802.11 b / g / n, 2.412GHz-2.484GHz
4G	Optional
Digital / Analog Input / Output	DI x 4, DO x 2, AI x 4
PT100 / PT1000	PT100 x 1, PT1000 x 1
DC Output Power	12V, 100mA
<b>Communication Protocol</b>	
Ethernet	Modbus-TCP, IEC 60870-5-104
RS485	Modbus-RTU, IEC 60870-5-103 (standard), DL / T645
<b>User Interface</b>	
LED	LED x 4
WEB	Embedded Web
USB	USB 2.0 x 1
<b>Mechanical</b>	
Dimensions (W x H x D mm)	255 x 47.5 x 173
Weight (kg)	0.8
Installation Method	Wall Mounting, DIN Rail Mounting, Tabletop Mounting
<b>Environment</b>	
Operating Temperature Range (°C)	-30 ~ +60
Storage Temperature Range (°C)	-40 ~ +70
Relative Humidity	5 ~ 95%
Max. Operating Altitude (m)	5000
Ingress Protection Rating	IP20

\*: Please visit GoodWe website for the latest certificates.

\*: All pictures shown are for reference only. Actual appearance may vary.