

Meiflex reinforced hoses for heating with galvanised braid and EPDM inliner.

- Reinforced hoses with galvanised steel wire braid for heating systems.
- Internal hose made from ageing-resistant EPDM (not impermeable), resistant against water and glycol-based antifreeze (max. 50%).

Advantages

- Flexible connections in certified quality.
- Prevents stresses and transmission of structure-borne noise.
- Numerous connection types.

Technical Specifications

- For temperatures between -5 and +110 °C.
- Operating pressures:

16 bar (up to 100 °C, up to DN32).

10 bar (up to 110 °C, up to DN32).

6 bar (up to 110 °C, from DN40).

- Connections: Brass, copper elbows, with union nut and flat gasket.
- The actual length compared with the length L declared by the supplier shall be within the following permissible tolerances, in compliance with standard EN 13618:

L ≤ 400 mm: +10 mm

400 mm < L ≤ 1000 mm: +20 mm

- 1000 mm < L ≤ 2000 mm: +30 mm



Description	Meiflex galv. 1 F/M x 300
Order Code	M4325.0134.30
GTIN	4016715001061
Model	<u>Meiflex Reinforced hoses for heating F x M</u>
Connection ["]	1" F x 1" M
Length* [mm]	300
Internal Ø [mm]	25
Weight [kg]	0,40

* Other lengths available upon request. Warning! In the event of condensation forming (risk of corrosion!), use stainless steel reinforced hoses!



Classification General Data

Etim Group	Hoses and hose cabinets
Etim Class	Flexible connecting hose (metal)
Product Name	None
Brand	Flamco
Product Type	MeiFlex
Order Code	M4325.0134.30
GTIN	4016715001061

Attributes

Material	Stainless steel
Material quality	Stainless steel 306 L (1.4404)
Inner diameter hose	25 mm
Connection 1	Internal thread
Nominal diameter connection 1	1 inch (25)
Outer pipe diameter connection 1	25 mm
Connection type connection 1	Straight
Connection 2	External thread
Nominal diameter connection 2	1 inch (25)
Outer pipe diameter connection 2	25 mm
Suitable for potable water	No
Connection type connection 2	Straight
Suitable for hot water	Yes
Suitable for cooled water	Yes
Suitable for central heating water	Yes
Suitable for glycol	Yes
Suitable for ethanol	Yes
Suitable for oil	No
Max. medium temperature (continuous)	110 °C
Max. pressure	16 bar
With braiding	Yes
Braiding galvanised	Yes
With sealing rings/gaskets	Yes
With conical nipple	No
Length	300 mm
Working length	300 mm
DVGW quality mark for water	No
Type approval according to BBR/EKS	No
Connection 1 thread size	1 inch
Connection 2 thread size	1 inch
Suitable for water	Yes

Find more information online:

[Packaging data](#)

Fort Blauwkapel 1
1358 DB, Almere - nl

T +31 (0)36 52 62 300
E info@aalberts-hfc.com
I flamco.aalberts-hfc.com