




25-026GASMG: Henco Standard Gas Ø26x3 with yellow pRotect. hose 25m



Commercial information

Certificates

DVGW Gas, GASTEC, TSU, ROST, UNI TS

Applications

Gas

Solutions

Building installations, Industry, Oil & gas, Utility, Shipbuilding

Technical characteristics

Material inner layer	Plastic	Outer pipe diameter	26 Millimetre
Quality class inner layer	PE-Xc	Wall thickness	3 Millimetre
Material intermediate layer	Aluminium	Medium temperature (continuous)	- Degrees celsius 20 6 0
Material outer layer	Plastic	Max. medium temperature (momentarily)	95 Degrees celsius
Quality class outer layer	PE-Xc	Max. operating pressure at 20 °C	16 Bar
Glass-fibre reinforced	✘	Max. operating pressure at max. medium temperature	10 Bar
Diffusion-proof	✓	Wall roughness	0.00 Millimetre 7
Nominal diameter	DN 20	Expansion coefficient	0.02 Millimetre per metre Kelvin 5
System specific	✓	Min. bending radius	78 Millimetre
Flexible	✓	Min. bending radius without tools	78 Millimetre
Suitable for surface mounting	✓	Outer diameter mantle pipe	36 Millimetre
Pipe colour	Yellow	Thickness of thermal insulation	0 Millimetre
With mantle pipe	✓	Lambda value	0.43 Watt per meter Kelvin
With heating cable	✘	Outer diameter thermal insulation	0 Millimetre
Colour outer sheath	Yellow	Outer width rectangular insulation	0 Millimetre
With thermal insulation	✘	Outer height rectangular insulation	0 Millimetre
SVGW certified	✘	Water content	0.31 Litre per metre 4
Capped	✘		
UV resistant	✘		
Halogen free	✓		
DIN-CERTCO certificate	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✓		
DVGW quality mark for water	✘		
Compliant with NF 545	✘		
KOMO certified	✘		
Type approval according to BBR/EKS	✘		

Related products