

RANA LINEAR S 3KLM NW OPAL 1-10 EM
0051285



Features

- Surface or Suspended LED Linear luminaire with Opal diffuser, Dimensions: 1150mm x 87mm x 87mm, Direct, White Body, 1-10V Dimmable, Emergency 3 hours maintained, Neutral White LED (4000K), 3210lm, 35W, 92lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse), Low LED Flicker (+/-5%), UGR<23, L90B10 at 50,000 hours, Electric Class1, Glow Wire Test 850°C


Product Overview

Product name	RANA LINEAR S 3KLM NW OPAL 1-10 EM
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Fixture rating	Enclosed
Environment	Internal
Fixture luminous flux (lm)	3210
Luminaire efficacy (lm/W)	91.71
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Glare control	< 23
Photobiological Risk Group	RG0
Total power consumption (W)	35
Electrical protection	Class I
Control gear type	Electronic ballast
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20

RANA LINEAR S 3KLM NW OPAL 1-10 EM
0051285


IK rating	IK01
Product EAN number	5410288512853
Warranty	5 years

Photometry



RANA LINEAR S 3KLM NW OPAL 1-10 EM
0051285

Technical drawings



Data table

GENERAL DATA

Product name	RANA LINEAR S 3KLM NW OPAL 1-10 EM
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Fixture rating	Enclosed
Environment	Internal
Operating temperature range (°C)	5°C...+30°C
Performance ambient temperature Tq (°C)	25
Warranty	5 years

RANA LINEAR S 3KLM NW OPAL 1-10 EM 0051285

OPTICAL DATA

Fixture luminous flux (lm)	3210
Luminaire efficacy (lm/W)	91.71
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Glare control	< 23
Photobiological Risk Group	RG0
Emergency duration (h)	3.0

ELECTRICAL DATA

Total power consumption (W)	35
Primary Supply/Product voltage - min (V)	220
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic ballast
Drive current (mA)	300
Inrush Current (A)	10
Inrush Duration (µs)	100
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Connectable conductor cross section - Min (mm²)	2.5
Connectable conductor cross section - Max (mm²)	2.5

LIFETIME DATA

Lifespan L70 B50	60000
------------------	-------

RANA LINEAR S 3KLM NW OPAL 1-10 EM 0051285

Lifespan L70 B20	60000
Lifespan L70 B10	60000
Lifespan L80 B50	60000
Lifespan L80 B20	60000
Lifespan L80 B10	60000
Lifespan L90 B50	60000
Lifespan L90 B20	60000
Lifespan L90 B10	60000

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK01
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1150
Nominal Product Width (mm)	87
Weight (kg)	3.55

PACKAGING

Single packaging type	Carton
Product EAN number	5410288512853
Packaging single width (cm)	10.5
Packaging single depth (cm)	10.0
DUN14 (outer)	05410288512853
Packaging outer length / height (cm)	116.5

SAFETY DATA

Optimal operating condition (°C)	5-30
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No