

## Data Sheet | Item Number: 281-470

Insulation stop; 0.08 - 0.2 mm<sup>2</sup> "s" (0.14 mm<sup>2</sup> "f-st"); 5 pieces/strip; white

<https://www.wago.com/281-470>



Color: ■ white

### Connection data

#### Connection 1

Strip length 9 ... 10 mm / 0.35 ... 0.39 inches

### Material data

Note (material data)

[Information on material specifications can be found here](https://www.wago.com/us/material-specifications)

Color	white
Fire load	0.025 MJ
Weight	0.8 g

### Commercial data

Product Group	1 (Rail Mounted Terminal Blocks)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	200 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332267335
Customs tariff number	39269097900

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Downloads**

**Environmental Product Compliance**

Compliance Search	
Environmental Product Compliance 281-470	<a href="#">↓</a>

**Documentation**

Additional Information		
Technical Section	pdf 2240.62 KB	<a href="#">↓</a>

Bid Text			
281-470	19.02.2019	xml 2.55 KB	<a href="#">↓</a>
281-470	28.04.2017	doc 23.50 KB	<a href="#">↓</a>


**CAD/CAE-Data**

CAD data	
2D/3D Models 281-470	<a href="#">↓</a>


CAE data	
WSCAD Universe 281-470	<a href="#">↓</a>
ZUKEN Portal 281-470	<a href="#">↓</a>

**Installation Notes**


### Conductor termination



Insert stripped, untwisted conductor into insulation stop.



The conductor is bundled.



The conductor insulation is prevented from being pushed into the clamping unit by the positive stop.