



EVBAFC20A	G4 Rack PDU BASIC		
FUNCTIONALITY	INPUT	OUTPUT	ENVIRONMENTAL
NONE	IEC 60309 C20 16A 100/240V 1.5MM^2 HO5 POWERCORD CABLE LENGTH: 3.0 M	(12) IEC 60320 C13 HIGH RETENTION / P-LOCK (12) EATON C39 - COMBO C13/C19 HIGH RETENTION / P-LOCK (C19 ONLY)	0° TO 60° C 32° TO 140° F
MECHANICAL	INPUT RATING	OUTPUT RATING	CERTIFICATIONS
1000mm (39.37") LENGTH 52mm (2.05") WIDTH 53mm (2.09") DEPTH ALUMINUM CHASSIS, BLACK	100-240V~ W+N+PE OR 2W+PE 16A 50/60HZ	100-240V~ 10A PER C13; 16A PER C39 16A MAX PER SECTION 16A MAX TOTAL	cTUVus, CE, UKCA, RCM
CIRCUIT BREAKERS	COMMUNICATION	ACCESSORIES	REGULATORY MODEL
NONE	NONE	SPARE PART ACCESSORY KIT SPK050	EBAF-JXFA-A31K

TOLERANCE GENERALE / GENERAL TOLERANCE		± 0.3	± 0°20'	VERIFIE PAR / VERIFIED BY	YS
TRAITEMENT / FINISH		NA		ECHELLE / SCALE	
MATIERE / MATERIAL		NA		1/2	
NIVEAU DU CERTIFICAT DE SOUMISSION REQUIS / SAMPLES APPROVAL PROCESS REPORT		X		DIMENSIONS AND TOLERANCES IN MILLIMETERS	
DESIGNATION		PDU G4 BA 0U C20 16A 1P 12xC13,12XC39		9001-22364_EVBAFC20A 01	
COTES A CONTROLER / INSPECTION DIMENSIONS		XX.X		NUMERO DU PLAN / PLAN NUMBER	
COTES FONCTIONNELLES / FUNCTIONAL DIMENSIONS		XX.X		DRAWING REV.	

Ce document est propriété de Eaton Industries Manufacturing GmbH. Duplication interdite sans autorisation.
This document is Eaton Industries Manufacturing GmbH property. Duplication forbidden without authorization.