



### Features

- Exterior LED Floodlight, comes complete with 1000mm flying lead and adjustable bracket, aluminium housing, clear glass diffuser, integrated anti-condensation valve, IP66, IK08, Class I, 3000K, CRI80, Non-dimmable, 3200lm, 23W, 139lm/W, Asymmetrical Wide beam, 100.000hrs L80B50 lifespan, 331 x 237 x 68mm (LxWxD) dimensions, 2.3kg weight, RAL9017 Traffic Black color.


### Product Overview

Product name	Kalani IP66 3KLM 830 ASYM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Other
General application	Logistics & Industry
ETIM Class	EC001744
Fixture luminous flux (lm)	3200
Luminaire efficacy (lm/W)	139
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	65x120
Photobiological Risk Group	RG1
Total power consumption (W)	23
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
LED Flickering Rate	Low (6% - 20%)

## Kalani IP66 3KLM 830 ASYM 0056801

Housing colour	RAL9017
IP rating	IP66
IK rating	IK08
Product EAN number	5410288568010
Warranty	5 years
Dimming method	N/A
Useful luminous flux (#use)	3200

### Photometry



### Technical drawings

