

Threefold faceplate, 71 mm centre distance, Niko Pure alu blue grey brushed

226-76700



Threefold faceplate with 71 mm centre-to-centre distance from the range Niko Pure.
Niko Pure alu blue grey brushed



Technical data

Threefold faceplate, 71 mm centre distance, Niko Pure alu blue grey brushed.

- Threefold faceplate for three switches.
- Colour faceplate: alu blue grey brushed
- Colour RAL (approximately): 240 30 05
- Colour NCS (approximately): NCS S 8005-R80B
- Recommended colour central plate: alu blue grey
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material finishing: The upperframe is made of aluminium. The lower frame is made of dark grey, blue grey coated polycarbonate (PC) + acrylic-styrene-acrylate (ASA).
- Surface treatment: anodised
- Surface finishing: matt
- Coating lower frame: enamelled blue grey
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Surface-mounting height: max. 8.5 mm
- Halogen-free: yes
- Fire safety:
 - self-extinguishing: complies with a filament test of 650°C
- Centre-to-centre distance: 71 mm
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Minimum ambient temperature: 5 °C
- Maximum ambient temperature: 40 °C
- Dimensions (HxWxD): 83 mm x 225 mm x 8.9 mm
- Dimensions visible (HxWxD): 83 mm x 225 mm
- Certification marks: KEMA, NF, SEMKO, ÖVE, CEBEC, VDE
- Marking: EU