

## 43P-161516: T-piece Press 16 x compression 15 x Press 16



### Commercial information

- Direct connection to Henco press 16 mm in copper or central heating pipe 15 mm
- Short installation length 2 x Press 16 mm x Compression 15 mm

### Basic unit dimensions

Height	49 mm
Length	95 mm
Width	26 mm
Net weight	0.139 kg

### Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, EMI

### Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Material connection 1	Brass	Angle	90 Degrees
Surface protection connection 1	Untreated	Outer pipe diameter connection 1	16 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 2	15 Millimetre
Material connection 2	Brass	Outer pipe diameter connection 3	16 Millimetre
Surface protection connection 2	Untreated	Wrench width	0 Millimetre
Surface treatment connection 2	Untreated	Max. operating pressure at 20 °C	16 Bar
Material connection 3	Brass	Wrench width union nut	0 Millimetre
Surface treatment connection 3	Untreated	Medium temperature (continuous)	-10 70 Degrees celsius
Model	T-piece	Standard Dimension Ratio (SDR)	0
Reducing	✘		
System specific	✔		
Connection 1	Press sleeve		
Connection 2	Compression ring		
Connection 3	Press sleeve		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
Main colour fitting	Brass		
High tensile strength	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✔		
With drain valve	✘		
With de-aerator	✘		
With thermal insulation	✘		
With buffer stud	✔		
Capped	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✔		
KIWA certified	✔		
Gastec QA mark	✘		
KOMO certified	✔		
Type approval according to BBR/EKS	✘		