

INSAVER SLIM 175 PIR

Insaver Slim UGR19 IP44 175 wide bezel 1050lm 830

0030442



Product features

- Insaver Slim is a ceiling recessed LED downlight (IP44 from the front), Die-cast aluminium body, loop in loop out connector for quick installation, Non dimmable LED driver, 9W; 1050lm; 117lm/W; 3000K; UGR <19 with shallow product depth 50mm. The bezel matches the look of PIR version (SKUs 0030320, 0030321). Meets TP(a) requirements.





PRODUCT OVERVIEW

Product name	Insaver Slim UGR19 IP44 175 wide bezel 1050lm 830
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Office, Retail
ETIM Class	EC001744
E-number FI	4278409
Warranty	5 years
Fixture luminous flux (lm)	1050
Luminaire efficacy (lm/W)	117
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	60
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	9
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK07
Product EAN number	5410288304427

PHOTOMETRY

INSAVER SLIM 175 PIR

Insaver Slim UGR19 IP44 175 wide bezel 1050lm 830
0030442



TECHNICAL DRAWINGS

