



Features


- 5 metre IP65 LED reel with pre-attached 3M adhesive type; equipped with 300 LEDs; 2250lm per 5m ; 24V; 3000K; CRI90; R9>50; SDCM≤3;Compatible with emergency packs: 0046600, 0046601




Product Overview

Product name	Flex Pro IP65 2250lm 930
Technology	LED
General application	Hospitality
ETIM Class	EC002706
Fixture luminous flux (lm)	2250
Luminaire efficacy (lm/W)	94
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Beam Angle (°)	120
Photobiological Risk Group	RG1
Power consumption (W)	24
Total power consumption (W)	24
Electrical protection	Class III
Dimmable	Yes
Housing colour	Transparent
IP rating	IP65
IK rating	IK00
Product EAN number	5410288681726
Warranty	5 years
Dimming method	Other
Useful luminous flux (#use)	2250

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	Flex Pro IP65 2250lm 930
--------------	--------------------------



Flex Pro IP65 2250lm 930
0068172

Technology	LED
General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002706
Warranty	5 years

OPTICAL DATA

Useful luminous flux (#use)	2250
Fixture luminous flux (lm)	2250
Luminaire efficacy (lm/W)	94
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Beam Angle (°)	120
Photobiological Risk Group	RG1

ELECTRICAL DATA

Power consumption (W)	24
Total power consumption (W)	24
Primary Supply/Product voltage - min (V)	24
Primary Supply/Product voltage - max (V)	24
Electrical protection	Class III
Control gear required	Yes
Dimmable	Yes
Dimming method	Other
Drive current (mA)	1000
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	N/A

LIFETIME DATA

Lifespan L70 B50	54000
------------------	-------

Flex Pro IP65 2250lm 930 0068172

Lifespan L70 B10	54000
Lifespan L80 B10	50000
Lifespan L90 B10	44000

PHYSICAL DATA

Housing colour	Transparent
IP rating	IP65
IK rating	IK00
Nominal Product Length (mm)	5000
Nominal Product Width (mm)	10
Nominal Product Height (mm)	4
Weight (kg)	0.2

PACKAGING

Product EAN number	5410288681726
Packaging single length / height (cm)	23.5
Packaging single width (cm)	22.5
Packaging single depth (cm)	3.0
DUN14 (inner)	15410288681723
Units per outer package	20
Packaging outer length / height (cm)	49.0
Packaging outer width (cm)	35.0
Packaging outer depth (cm)	24.0


SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No

Energy label



0068172




24
kWh/1000h



2019/2015



0068172



24
kWh/1000h



2019/2015