

Product data sheet

Item No. 93.042.0258.0

Male connector ST17/2 SR WS

Device connectors, snap-in panel mount, ST17/2, 2 pole, male, spring clamp connection, 50V/16A, color of coding: white



Item No.	93.042.0258.0
EAN	4015573239173
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

**General**

Rated current	16 A
Rated voltage	50 V
Pollution degree	2
Mechanical coding	Yes
Rated impulse voltage	4 kV
Interlockable	Yes
Color of coding/ contact carrier	White
Marking of poles	

**Connection Data**

Connection cross section solid	2.5 mm <sup>2</sup>
Cross section solid 2	0.5 mm <sup>2</sup>
Connection cross section stranded	1.5 mm <sup>2</sup>
Cross section stranded 2	0.5 mm <sup>2</sup>
Terminations per pole	2

**Model**

Model	male
-------	------

Number of poles	2
Connection type	Tension clamp connection
Connecting thread metric	No thread
Angle of plug	Straight
Degree of protection (IP)	IP20
Remark to type of connection	Finely stranded con. req. Wieland cable end sleeve
Thickness of housings (electrical device) 2	0.5 mm
Thickness of housings (electrical device)	1.5 mm
Built-in component	Snap-in

**Material**

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Tin-plated

**Dimensions**

Length	37 mm
Width	25 mm
Height	18.5 mm

**Technical drawing**

