



Electrical data

Specialty functions	With shield connection
---------------------	------------------------

Safety and protection

Protection type	IP20
-----------------	------

Connection Data

Mating cycles	750
Connection Cable	Cat. 6A (min.)

Connection 1

Pluggable connector	RJ-45 (shielded)
Pole number 1	8
Connection type	System

Connection 2

Connector	RJ-45 (shielded)
Pole number	8
Connection type	System

Physical data

Width	18 mm / 0.709 inches
Height	90 mm / 3.543 inches
Depth from upper-edge of DIN-rail	59 mm / 2.323 inches

Mechanical data

Mounting type	DIN-35 rail
Housing design	Mounting carrier
Mating cycles	750

Material data

Contact material (connector)	Spring steel
Fire load	0 MJ
Weight	34 g

Environmental requirements

Ambient temperature (operation)	-10 ... +60 °C
Ambient temperature (storage)	-40 ... +70 °C
Relative humidity	≤ 95 % (non-condensing)

Commercial data

PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	PL
GTIN	4066966083491
Customs tariff number	85369010000

Product Classification

UNSPSC	39121421
ETIM 9.0	EC002780
ETIM 10.0	EC002780
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 289-198



Documentation

Bid Text		
289-198	xml 3.68 KB	↓
289-198	docx 14.79 KB	↓

CAD/CAE-Data

CAD data	
2D/3D Models 289-198	↓

CAE data	
EPLAN Data Portal 289-198	↓