

## UFH-060511-MD: 11-groups Manifold brass,adjustable,with flow meters



### Commercial information

Brass manifold for both housing and utility buildings. It is compact in construction and allows smooth installation. This manifold is equipped with flowmeters and fine regulating valves for each circuit. Outlets are connected to eurocone3/4".

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 320 mm   |
| Length     | 610 mm   |
| Width      | 100 mm   |
| Net weight | 5.150 kg |

#### Certificates

#### Applications

Heating, Cooling, Underfloor Heating

#### Solutions

Underfloor heating, Building installations, Industry, Utility

## Technical characteristics

|                                       |                                                |                                                |                      |
|---------------------------------------|------------------------------------------------|------------------------------------------------|----------------------|
| Connection type primary side          | 2-pipe                                         | Outer pipe diameter primary connection         | 32 Millimetre        |
| Suitable for cooling                  | ✓                                              | Medium temperature (continuous)                | 0 80 Degrees celsius |
| Material                              | Brass                                          | Max. operating pressure                        | 6 Bar                |
| Position primary connection           | Left/right                                     | Max. number of expansion groups                | 0                    |
| Primary connection                    | External thread cylindrical BSPP-G (ISO 228-1) | Number of groups secondary                     | 11                   |
| Nominal diameter primary connection   | 1 inch (25)                                    | Outer pipe diameter secondary                  | 12 20 Millimetre     |
| With valves on primary connection     | ✗                                              | Flow-through capacity                          | 0 6 Litre per hour   |
| With mixing valve                     | ✗                                              | Min. pressure difference secondary flow/return | 0 Kilo Pascal        |
| Expandable                            | ✗                                              | Width                                          | 100 Millimetre       |
| Multi-zone manifold                   | ✗                                              | Height                                         | 320 Millimetre       |
| With temperature limit                | ✗                                              | Depth                                          | 610 Millimetre       |
| With non-return valve                 | ✗                                              |                                                |                      |
| With circulation pump                 | ✗                                              |                                                |                      |
| Article compression class             | PN 6                                           |                                                |                      |
| With controller                       | ✗                                              |                                                |                      |
| Hydraulic balance control             | None                                           |                                                |                      |
| Volume flow measurement               | Analogue                                       |                                                |                      |
| With thermometer                      | ✗                                              |                                                |                      |
| Temperature measurement supply        | None                                           |                                                |                      |
| Temperature measurement return        | None                                           |                                                |                      |
| With de-aeration                      | ✗                                              |                                                |                      |
| With pressure gauge                   | ✗                                              |                                                |                      |
| Secondary connection                  | Euroconus standardless                         |                                                |                      |
| Nominal diameter secondary connection | 3/4 inch (20)                                  |                                                |                      |
| Closable groups                       | ✓                                              |                                                |                      |
| With flow-through indicator           | ✓                                              |                                                |                      |
| With thermal actuator                 | ✗                                              |                                                |                      |
| With wall-mounting bracket            | ✓                                              |                                                |                      |
| With casing                           | ✗                                              |                                                |                      |