

UFH-0405CDHC03: 3-groups manif.comp. h/c, adjustable with flow meter



Commercial information

Certificates

Applications

Heating, Cooling, Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Utility

Technical characteristics

Connection type primary side	2-pipe	Number of floor heating groups	3
Connection central heating	External thread	Max. operating pressure	4 Bar
Suitable for cooling	Yes	Max. number of expansion groups	0
Material	Plastic	Width	540 Millimetre
Nominal diameter central heating	DN 15	Height	195 Millimetre
Position primary connection	Bottom	Depth	460 Millimetre
Nominal diameter primary connection	1/2 inch (15)		
With valves on primary connection	No		
Expandable	No		
Hydraulic balance control	None		
With thermometer	Yes		
Temperature measurement supply	Analogue		
Temperature measurement return	Analogue		
With de-aeration	No		
With pressure gauge	No		
With filling/drain tap	Yes		
Closable groups	Yes		
With flow-through indicator	Yes		
With wall-mounting bracket	Yes		
With casing	No		

Related products

Product code	GTIN	Description
BE40	05414764221369	Henco Jaws (universal) BE-Profile 40x3,5
UFH-C190118	05414764221369	Henco Flowmeter 0-480 L/H Adjustable For CD
UFH-TM050-M	05414764221369	Henco Thermometer for return with EK connections

Image

